

| MODEL | | | Space 1 | |
|--|-------------------------------|-----------|--|-----------------|
| MAXIMUM POWER | LINE CONDITIONER SYSTEM | | 1,000~2000 W (UPON USAGE OF THE POWER ISOLATOR SYSTEM) | |
| | POWER ISOLATOR SYSTEM | | 1,000 W | |
| | TOTAL | | 2,000 W | |
| INPUT | | | | |
| VOLTAGE | | | 220~240 V | |
| FREQUENCY | | | 50 Hz | |
| AC POWER CORD | TYPE | | PVC INSULATION, COMPLY TO UL, CSA STANDARD | |
| | WIRE SIZE x LENGTH | | 14 AWG x 2.5 M | |
| PLUG | | | 3 POLE NEMA 5-15P TYPE | |
| OUTPUT | | | | |
| VOLTAGE | | | 220~240 V | |
| LINE CONDITIONER | | | | |
| TRANSIENT VOLTAGE SURGE SUPPRESSION | | | VARISTOR | |
| RFI AND EMI FILTER | | | X2, Y2 CAPACITOR, POWER CAPACITOR, TOROIDAL COIL | |
| HIGH SURGE AND LIGHTNING PROTECTION | | | LIGHTNING GAS ARRESTER NOMAL IMPULSE DISCHARGE CURRENT 5 kA AT 8/20 μs SINGLE IMPULSE DISCHARGE CURRENT 10 kA AT 8/20 μs | |
| RECEPTACLE | ISOLATED GROUND NEMA 5-20R | TOTAL | FILTER SYSTEM | ISOLATED SYSTEM |
| | | 6 OUTLETS | 2 OUTLETS | 4 OUTLETS |
| PROTECTION SYSTEM | | | | |
| OVERLOAD AND OUTPUT SHORT CIRCUIT PROTECTION | | | FUSE | |
| DISPLAY | | | | |
| OPERATION ON STATUS | | | BLUE LED AT POWER IS LIGHT | |
| GROUNDING SYSTEM OF INPUT POWER STATUS | | | BLUE LED AT GROUND IS LIGHT | |
| GENERAL | | | | |
| OPERATION ON/OFF | | | POWER SWITCH | |
| STRUCTURE | | | | |
| DIAL | | | ANODIZED ALUMINUM | |
| BODY | | | GALVANIZED SINK METAL 1.2 mm WITH SPECIAL GRADE COLOR COATING | |
| COVER | | | ALUMINUM 1.5 mm WITH SPECIAL GRADE COLOR | |
| NATURAL RUBBER BASE | | | SOFA, EPDM/80 | |
| SCREWS AND NUTS | | | STAINLESS STEEL | |
| WIRING | | | THE ALPHABHRET DIRECTION WITH THE STAR CIRCUIT SYSTEM TO EACH RECEPTACLE | |
| PHISICAL | | | | |
| AMBIENT TEMPERATURE | | | 0~50 °C | |
| RELATIVE HUMIDITY | | | 0~95 % | |
| DIMENSION (W x H x D) | | | 305 x 210 x 270 mm | |
| NET WEIGHT | | | 25 kg | |

Specifications are subject to change without prior notice. This item can change by customer's requirement.

NUMBER : CTSpace1 EN 1

SILICON POWER SUPPLY Co., Ltd.

455/13-16 Soi Phibunuppatham, Latphrao Road, Samsennok, Huaykwang, Bangkok 10320
TEL: 0-2275-1182, 0-2275-1275, 0-2275-7161, 0-2276-9973 FAX: 0-2275-7309 10320

Website: www.sidital.com
Website: www.siliconthai.com
E-mail: info@siliconthai.com
ISO 9001:2008 Certified